

GROUND-mini



IRG1-1R-120H(231)

Application

A compact inground marker light fixture designed for both functional and decorative illumination purposes.



Light color	Red
CRI	
Color binning	±3 nm
Optics, degrees	120
Delivered lumens, lm	10
Voltage, V	230 AC 50 Hz
Wattage, W	1,5
Power factor	> 0,9
Electric class	I (first)
Protection class	IP67
Operating temperature, degrees C	-40 ... +55
IK rating	IK10
Control, protocols	On/Off
Control, pixel size	
Lifespan, hours	Not less than 50 000
Warranty, years	5
Dimensions, mm	Ø88x97
Weight, kg	0,53
Content of delivery	Luminaire, package, passport, mounting instructions



Mounting

In-ground

Materials

Housing — aluminum casting alloy, covered with powder paint; protective glass — silicate tempered glass, 8 mm thick, with silicon sealer; mounting curb – polypropylene; decorative frame — polished stainless steel; metalware — stainless steel.

Integrated technologies

Aquatech® technology – a multi-stage protection technology safeguards luminaires against water ingress.

Additional codes definition

- (131) - Transparent hardened glass, round frame, 90 mm diameter;
- (141) - Transparent hardened glass, square frame, 90 mm side length;
- (231) - Matte hardened glass, round frame, 90 mm diameter;
- (241) - Matte hardened glass, square frame, 90 mm side length.

Accessories

Customized accessories are manufactured according to the project

Compatible control system devices