

LINEUP

ILG6-2FC-15x60RH-60

Application

The LINEUP inground linear luminaire is expertly engineered to meet the unique installation and operational challenges of demanding environments. By blending the flexibility of LINE configurations with cutting-edge technology, it boasts a robust, precision-crafted housing designed for seamless ground installation. Whether deployed as a continuous light line or as a standalone unit, this luminaire delivers exceptional visual comfort, thanks to its integrated anti-glare grill.



L, mm
656
956
1256

Light color	multichip RGBW65	
CRI	>80	
Color binning	±3 nm, 2 MacAdam steps	
Optics, degrees	15x60	
Delivered lumens, lm	Red	85
	Green	430
	Blue	75
	White	650
	Full color	420
Voltage, V	230 AC 50 Hz	
Wattage, W	22	
Power factor	> 0,9	
Electric class	I (first)	
Protection class	IP67	
Operating temperature, degrees C	-40 ... +55	
IK rating	IK10	
Control, protocols	DMX-512 + RDM	
Control, pixel size	1 luminaire = 1 pixel	
Lifespan, hours	Not less than 50 000	
Warranty, years	5	
Dimensions, mm	656x121x110	
Weight, kg	3,9	
Content of delivery	luminaire, package, passport, mounting instructions	

Mounting

In-ground

Materials

Housing — extruded aluminum section with galvanic coating, covered with powder paint; protective glass — silicate tempered glass, 8 mm thick; end caps — aluminum casting alloy with galvanic coating, covered with powder paint; mounting curb — extruded polypropylene profile; end caps of the recessed mounting box — stainless steel; decorative frame — polished stainless steel; metalware — stainless steel.

Integrated technologies

ColorPro® technology is a software algorithm that optimizes the use of the luminaire's available power to deliver peak brightness.

EternalTechnology® is a continuous monitoring of the internal temperature of the lighting fixture through the system of integrated sensors.

Truelight® technology - a comprehensive suite of solutions designed to deliver flawless lighting effects.

Aquatech® technology – a multi-stage protection technology safeguards luminaires against water ingress.

COOLight® technology is aimed at increasing the efficiency of lighting fixtures.

Additional codes definition

Accessories

Customized accessories are manufactured according to the project

Compatible control system devices

LightCAD software key x2

LightCAD software key x8

LightCAD software key x32

LightCAD software key x64

LightCAD software key x128

LightCAD software key x512

Controller LED-IPCe

Controller LED-IPCs

Converter U-Box 8

Converter U-Box 4

Converter Din-Box 8

Converter Din-Box 6

Converter Din-Box 2

Splitter DMX (B1T2)

Splitter DMX (B4)

Converter UCS-ILCS