INTILED

SITE

IMF16-1,5W40-40a110H

Application
A professional light fixture designed to illuminate open spaces surrounding the building, such as parking lots, local areas, and entrance zones. It comes equipped with accessories for installation on various types of supports, making it suitable for lighting parks and recreational areas. The standard version, with a power output of 25W, enables effective placement of the luminaire at heights of up to 5 meters.

IP66 IK08

Standard RAL colors

1015 1001 8004 8017

9005 7016 9006 9003

Standard coating type
moire

Light color	White 4000 K
CRI	> 80
Color binning	2 MacAdam steps
Optics, degrees	40a110
Delivered lumens, lm	2 800
Voltage, V	230 AC 50 Hz
Wattage, W	25
Power factor	> 0,9
Electric class	I (first)
Protection class	IP66
Operating temperature, degrees C	-40 ... +55
IK rating	IK08
Control, protocols	On/Off
Control, pixel size	
Lifespan, hours	Not less than 50 000
Warranty, years	5
Dimensions, mm	210x393x48
Weight, kg	4,8
Content of delivery	Luminaire, package, passport, mounting instructions





Mounting
Surface mounted

Materials
Luminaire, bracket — cast aluminum;
diffuser — silicate glass.

Integrated technologies
None

Additional codes definition

Accessories
Bollards, brackets

Compatible control system devices